



KEY FEATURES

- Built for Precision
 - Integrated with advanced temperature & humidity monitoring features, the Camden chambers ensure precise drying conditions for various wood types.
- Fully Integrated Turn-Key Solution

 The Camden Series offers complete, ready-touse kiln packages that include all necessary
- components for immediate operation.

 User-Friendly Controls

 Featuring intuitive control systems, the Camden
- Series allows for easy monitoring and precise adjustments, ensuring optimal drying performance.
- Robust Construction

 Built with high-quality, durable materials, the Camden Series Chambers are designed to withstand the demands of continuous kiln operation, providing long-lasting reliability.

About The Camden Series Kilns

Medium-sized kiln operations now have a better option. Nyle has created a set of easy-to-assemble kiln packages that include a chamber with a dehumidification system sized to meet your lumber drying needs.

Designed to the same standards as our larger custom kilns, these kits are semi-assembled packages that can be easily erected on your site.

TECHNICAL DATA SPECIFICATION

	Camden 8	Camden 15	
Chamber Footprint	21' W x 22' D x 15' 4" H	29' W x 34' 6" D x 16' 7" H	
Load Space	19' W x 16' D x 10' 6" H	27' W x 17' 4" D x 12' 6" H	
Drying Temperature	Up to 160° F		
Approximate Capacity	8,000-10,000 BF	12,000 - 20,000 BF	
Equipment*	HT 8	HT 8	HT 18
Auxiliary Heat	12 kW	12 kW	48 kW
Compressor Nominal HP	5 HP	5 HP	15 HP
Internal Blower Motors	1.5 HP	1.5 HP	3 HP
Over Temperature Vents	Four (14" x 16")	Four (20" x 20")	
Circulating Fans	Six 1/2 HP 24"	Six 1/2 HP 24"	
Power Requirements	480V / 3 Phase / 60 Hz 70 A Required.	480V / 3 Phase / 60 Hz 70 A Required.	480V / 3 Phase / 60 Hz 150 A Required.

^{*}Camden 15 also available in a gas version



